

Hose Heavy Duty up to 212 °F / 100 °C iØ 3/8" black

Part No.:	901006
Material:	Rubber with fiber braided reinforcement
Color:	Black
Dimensions:	
Outer diameter:	0.625" (15.9 mm)
Inner diameter:	0.375" (9.5 mm)

Mechanical properties:

Excellent flexibility, Leak-proof protection without crimping. Outer layer of synthetic rubber with abrasion, ozone, and weather resistance. MSHA Approved.

Chemical properties:

Resistance to hydraulic fluids based on mineral oil, lubricating oil, coolant, antifreeze, air, water and water-oil.

Technical data:	SAE 100R6 / EN 854 R6
Max operating pressure at +68°F (+20°C)	400 psi (28.0 bar)
Burst Pressure at +68°F (+20°C)	1600 psi (110.0 bar)
Minimum bending radius at +68°F (+20°C)	3.0" (76.2 mm)
Operating Temperature Range	-40°F to 212°F (-40°C to 100°C)

Warning: It is important to use the correct fitting with any hose product to ensure a proper connection. Only use the fittings suggested by perma for this hose product. Maximum fittings and hoses by different manufacturers can lead to an unstable connection, due to difference in manufacturing techniques and tolerances. Such connections can fail and have the potential to spray and cause personal injury or property damage.

